



LETTER TO THE EDITOR

A NEW HYSTERETIC DAMPING MODEL?

Stephen H. Crandall
Massachusetts Institute of Technology
Cambridge, MA 02139

(Received 11 November 1994)

In [1] a new solution for the free vibration of a single mass and spring system with ideal hysteretic damping is proposed. The purported solution, which is constructed from piecewise harmonic motions, forms a smooth shrinking spiral in the phase plane. The segments in the first and third quadrants are free undamped vibrations of the same mass on a slightly stiffer spring while the segments in the second and third quadrants are free undamped vibrations of the same mass on a slightly softer spring. Nonzero motion derivatives of second and higher orders are discontinuous across the joints between segments. The segments of this ingenious solution are exact solutions to Eq.(9) of [1]. They are however unrelated to the original hysteretic system because Eq.(4), from which Eq.(9) follows, is not the time-domain equivalent of the frequency-domain equations in Eq.(2) and Eq.(5). The real parts of the complex phasors $\bar{u}e^{i\omega t}$ and $\bar{P}e^{i\omega t}$ which satisfy Eq.(2) and Eq.(5), do not satisfy Eq.(4).

The correct time-domain equivalent is provided by a Fourier transform of the frequency-domain relation as explained in [2] and [3]. The proposal in [1] continues a long line [4,5] of attempts to produce time-domain representations of ideal hysteric damping by heuristic reasoning. The free vibrations predicted by [1] share some similarities with the exact solution [6,7] for the hysteretically damped oscillator. The damped natural frequency is correct to first order in η but the first-order term in the decrement is too small by a factor of about $2/\pi$. The procedure of [1] provides no hint of the major flaw in the ideal hysteretic model: the noncausal response property. This property was discovered, independently, in the early sixties by Fraeijs de Veubeke [8], Caughey [9], and Crandall [6].

References

1. L.Y. Chen, J.T. Chen, C.H. Chen, and H.K. Hong, Free vibrations of a SDOF system with hysteretic damping, *Mech. Res. Comm.* 21, 599-604 (1994).
2. S.H. Crandall, The role of damping in vibration theory, *J. Sound & Vib.* 11, 3-18 (1970). Reprinted in *Vibration-Beams, Plates and Shells, Benchmark Papers in Acoustics*, Vol. 8, pp. 364-380 (1976).
3. S.H. Crandall, The hysteretic damping model in vibration theory, *J. Mech. Engrg. Sci., Proc. I. Mech. E.* 205C, 23-28 (1991).
4. See references 17-26 in [2] above.
5. R.E.D. Bishop and W.G. Price, A note on hysteretic damping, pp. 39-45 in *Random Vibration-status and recent developments*, Elsevier, Amsterdam(1986).
6. S.H. Crandall, Dynamic response of systems with structural damping pp. 183-193 in *Air, Space and Instruments*, McGraw-Hill, New York (1963).
7. L. Gaul, Structural damping in frequency and time domain. Proc. 7th Intl Modal Analysis Conf. 1989, pp. 177-184.
8. B.M. Fraeijs de Veubeke, Influence of internal damping on aircraft resonance, Chapter 3 in *AGARD manual on elasticity* (1960).
9. T.K. Caughey, Vibration of dynamic systems with linear hysteretic damping, pp. 87-97 in *Proc. Fourth U.S. Natl. Cong. Appl. Mechs.* ASME (1962).